

SELF PRIMING PUMP (FPSP)

SPECIFICATIONS

Version	:	Single Phase AC, 50 Hz
Speed	:	2800 rpm
Voltage Range	:	180 - 240 V*
Maximum Suction Head (with NRV)	:	6 m (20 ft)
Maximum Liquid Temperature	:	40 °C
Maximum Ambient Temperature	:	45 °C



Models	Power		Pipe Size Suction x Delivery (mm)		Capacitor (mfd)	Gross* Weight (kg)	Total head in meters / Feet Vs Discharge in LPH										
							m	6	9	12	18	24	33	36	39	42	45
	ft	20					30	40	60	80	110	120	130	140	150		
FPSP 30H	0.5	0.37	25	25	10	8.1		2520	1980	1780	1440	1180	810	720	-	-	-
FPSP 40H	1.0	0.75	25	25	25	11.2		4300	3600	3300	2900	2440	1140	900	800	680	500

CENRIFUGAL MONOBLOCK PUMP (FPM)

SPECIFICATIONS



Version	:	Single Phase AC, 50 Hz
Speed	:	2800 rpm
Voltage Range	:	180 - 240 V*
Maximum Suction Head (with NRV)	:	7.5 m (25 ft)
Maximum Liquid Temperature	:	40 °C
Maximum Ambient Temperature	:	45 °C

Models	Power		Pipe Size Suction x Delivery (mm)		Capacitor (mfd)	Gross* Weight (kg)	Total head in meters / Feet Vs Discharge in LPH										
							m	3	6	9	12	14	15	18	21	24	27
	ft	10					20	30	40	45	50	60	70	80	90		
FPM 21HH	0.5	0.37	25	25	15	13.5		*	*	*	5000	4600	4100	2400	1600	1100	-
FPM 16LH	0.5	0.37	25	25	12.5	12.5		*	*	6100	5700	3600	2500	1200	-	-	-

PERIPHERAL PUMP (FPP)

SPECIFICATIONS

Version	: Single Phase AC, 50 Hz
Speed	: 2800 rpm
Voltage Range	: 180 - 240 V*
Maximum Suction Head (with NRV)	: 6 m (20 ft)
Maximum Liquid Temperature	: 50°C
Maximum Ambient Temperature	: 55 °C



Models	Power		Pipe Size Suction x Delivery (mm)		Capacitor (mfd)	Gross* Weight (kg)	Total head in meters / Feet Vs Discharge in LPH										
	H.P.	kW					m	6	9	12	18	24	33	36	39	42	45
							ft	20	30	40	60	80	110	120	130	140	150
FPP 90H	0.5	0.37	25	25	10	5.9		2480	1920	1720	1400	1120	780	680	-	-	-
FPP 150H	1.0	0.75	25	25	25	10.7		4240	3580	3240	2860	2410	1120	880	760	620	480

OPENWELL SUBMERSIBLE PUMP

SPECIFICATIONS



Version	: Single Phase AC, 50 Hz
Speed	: 2800 rpm
Voltage Range	: 180 - 240 V*
Maximum Liquid Temperature	: 40 °C

Models	Power		Pipe Size Suction x Delivery (mm)		Capacitor (mfd)	Gross* Weight (kg)	Total head in meters / Feet Vs Discharge in LPH									
	H.P.	kW					m	6	9	12	14	18	21	24	27	30
							ft	20	30	40	45	60	70	80	90	100
FPOW 90H	1.0	0.75	32	25	50	24		18000	16500	15200	13600	9300	8600	5300	2100	-

FORSER INDUSTRIES Pvt Ltd

No. 37, Venugopal Pillai Layout, Palaiyur, P.N. Palayam, Coimbatore - 641 037

Phone : 0422 - 4960566 | E-mail : info@forserpumps.com | Web : www.forserpumps.com